

V200 'Zero' Client

Zero Client for PCoIP® Thin Computing



Front View

Rear Panel

The Vtona V200 zero client delivers a complete desktop experience for even the most advanced user. Incorporating the Teradici TERA2321 PCoIP® Processor, the Vtona V200 ensures a rich multi-media experience supporting 3D graphics, CAD, video and more.

Designed to support VMware Horizon View™, the Vtona V200 has no operating system and is simple to implement and manage, with enhanced security protection from viruses and malware.

Energy efficient and with a small desktop footprint, the Vtona V200 comes complete with full USB and audio peripheral connectivity, dual DVI for multi-monitor support and is capable of a maximum screen resolution of 1920 x 1200.

Backed by VXL's comprehensive worldwide support network, the Vtona V200 also comes with an impressive standard three-year warranty.

The Vtona V200 represents an unbeatable combination of affordability, quality, performance and service.

Key Features

- Teradici TERA2321 PCoIP® Processor for a rich multi media experience
- Dual DVI with resolution up to 1920x1200
- Onboard 512 MB DDR3 memory
- Very small footprint -150mm (H) x 130mm (D) x 45mm (W)
- Highly reliable fanless design - very low power consumption
- 4 USB 2.0 ports (2 Front / 2 Rear)
- Built-in Gigabit RJ45 Ethernet



V200 'Zero' Client

Zero Client for PCoIP® Thin Computing



Technical specification

Processor

- Teradici TERA2321 PCoIP®

System Memory

- RAM : Onboard 512MB DDR3-1333

Display Support

- One DVI display with a maximum of 2560x1600 resolution using an external custom dual-link DVI cable
- Or
- Two DVI display, each with a maximum of 1920x1200 resolution

Rear Panel

- 2 x USB 2.0
- Ethernet Port
- 1 x DVI-I
- 1 x DVI-D
- Kensington Security Slot
- 1 x 3.5 mm Speaker jack
- DC power input

Front Panel

- Power Button
- 2 x USB
- 1 x 3.5 mm Headphone jack
- 1 x 3.5 mm Microphone jack

External Power Adapter

- Worldwide auto-sensing 100-240 V AC
- DC output 12V, 2A

Power Consumption

- Idle state : 6 W

Networking

- Auto-sensing 10/100/1000 Mbps Gigabit LAN Or
- Optical : Fibre at 100/1000 Mbps
- Wake On LAN

Operating Environment

- Operating Temperature: 0 to 40°C
- Storage Temperature: -20 to 60°C
- Humidity: 20% to 80% maximum, non-condensing

Optional Accessories

- Dual single-link DVI to one dual-link DVI cable
- Power cord (country specific)

Physical Characteristics

- Dimension (HxDxW): 150 x 130 x 45 mm
- Weight : 1.5 kg

Regulatory Compliance

Safety and EMC:

- CE, FCC, cULus, TUV-GS, C-tick, CCC

Energy and Environment:

- WEEE, RoHS

Warranty

- Three years limited warranty